

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SOLID POWER XL

Other means of identification : Not applicable.

Recommended use : Machine Warewashing Detergent

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : 0.06 % - 0.156 %

Company : Ecolab New Zealand
2 Daniel Place
Te Rapa, Hamilton New Zealand
+64 7 958 2319

Emergency telephone number : 0800 243 622 (0800 CHEMCALL)

Issuing date : 09.10.2014

Section: 2. HAZARDS IDENTIFICATION
HSNO Hazard classification
Product AS SOLD

Acute toxicity (Oral) : 6.1 D
Acute toxicity (Dermal) : 6.1 D
Skin corrosion : 8.2 B
Serious eye damage : 8.3 A
Aquatic toxicity (Acute or Chronic) : 9.1 D
Ecotoxic to terrestrial vertebrates : 9.3 C

Product AT USE DILUTION

Not a hazardous substance or mixture.

GHS Label element
Product AS SOLD

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Harmful if swallowed.
Harmful in contact with skin.
Causes severe skin burns and eye damage.
Harmful to aquatic life.
Harmful to terrestrial vertebrates.

Precautionary Statements : **Prevention:**
Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective

SAFETY DATA SHEET

SOLID POWER XL

gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Specific measures (see supplemental first aid instructions on this label). Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Product AT USE DILUTION

Precautionary Statements

Prevention:

Wash hands thoroughly after handling.

Response:

Get medical advice/ attention if you feel unwell.

Storage:

Store in accordance with local regulations.

Other hazards

: None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product AS SOLD

Pure substance/mixture : Mixture

Chemical Name

sodium hydroxide

CAS-No.

1310-73-2

Concentration: (%)

60 - 100

Product AT USE DILUTION

No hazardous ingredients

Section: 4. FIRST AID MEASURES

Product AS SOLD

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal

SAFETY DATA SHEET

SOLID POWER XL

protective equipment.

Notes to physician : Treat symptomatically.

Product AT USE DILUTION

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

See toxicological information (Section 11)

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

Specific hazards during firefighting : Exposure to decomposition products may be a hazard to health.

Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
Sulphur oxides

Special protective equipment for firefighters : Use personal protective equipment.

Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Hazchem Code : 2W

Section: 6. ACCIDENTAL RELEASE MEASURES

Product AS SOLD

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SAFETY DATA SHEET

SOLID POWER XL

Product AT USE DILUTION

- Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : No special environmental precautions required.
- Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AS SOLD

Emergency Management Trigger Levels

The following trigger level applies:

- Emergency Plan : 1,000 kg
- Signage : 250 kg

Section: 7. HANDLING AND STORAGE

Product AS SOLD

- Advice on safe handling : Do not ingest. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not get in eyes, on skin, or on clothing.
- Conditions for safe storage : Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Storage temperature : -10 °C to 50 °C

Product AT USE DILUTION

- Advice on safe handling : Wash hands after handling. For personal protection see section 8.
- Conditions for safe storage : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product AS SOLD

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
sodium hydroxide	1310-73-2	WES-Ceiling	2 mg/m ³	NZ OEL

- Engineering measures : Effective exhaust ventilation system Maintain air concentrations below occupational exposure standards.

Personal protective equipment

- Eye protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

SAFETY DATA SHEET

SOLID POWER XL

- Hand protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.
- Skin protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.
- Respiratory protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

- Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

- Eye protection : No special protective equipment required.
- Hand protection : No special protective equipment required.
- Skin protection : No special protective equipment required.
- Respiratory protection : No personal respiratory protective equipment normally required.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

	Product AS SOLD	Product AT USE DILUTION
Appearance	: Cast Solid	liquid
Colour	: opaque, white	colourless
Odour	: odourless	odourless
pH	: 12.5 - 12.8, 1 %	10.11 - 10.91
Flash point	: Not applicable.	
Odour Threshold	: no data available	
Melting point/freezing point	: no data available	
Initial boiling point and boiling range	: no data available	
Evaporation rate	: no data available	
Flammability (solid, gas)	: no data available	
Upper explosion limit	: no data available	
Lower explosion limit	: no data available	
Vapour pressure	: no data available	
Relative vapour density	: no data available	
Relative density	: no data available	
Water solubility	: no data available	

SAFETY DATA SHEET

SOLID POWER XL

Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, kinematic	: no data available
Explosive properties	: no data available
Oxidizing properties	: no data available
Molecular weight	: no data available
VOC	: no data available

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: Acids Metals Organic materials
Hazardous decomposition products	: Decomposition products may include the following materials: Carbon oxides Sulphur oxides

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Eye contact, Skin contact

Potential Health Effects

Product AS SOLD

Eyes	: Causes serious eye damage.
Skin	: Harmful in contact with skin. Causes severe skin burns.
Ingestion	: Harmful if swallowed. Causes digestive tract burns.
Inhalation	: May cause nose, throat, and lung irritation.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes	: Health injuries are not known or expected under normal use.
Skin	: Health injuries are not known or expected under normal use.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Health injuries are not known or expected under normal use.

SAFETY DATA SHEET

SOLID POWER XL

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion
Skin contact : Redness, Pain, Corrosion
Ingestion : Corrosion, Abdominal pain
Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact : No symptoms known or expected.
Skin contact : No symptoms known or expected.
Ingestion : No symptoms known or expected.
Inhalation : No symptoms known or expected.

Toxicity

Product AS SOLD

Acute oral toxicity : Acute toxicity estimate : 775.57 mg/kg
Acute inhalation toxicity : no data available
Acute dermal toxicity : Acute toxicity estimate : 1,706 mg/kg
Skin corrosion/irritation : no data available
Serious eye damage/eye irritation : no data available
Respiratory or skin sensitization : no data available
Carcinogenicity : no data available
Reproductive effects : no data available
Germ cell mutagenicity : no data available
Teratogenicity : no data available
STOT - single exposure : no data available
STOT - repeated exposure : no data available
Aspiration toxicity : no data available

Section: 12. ECOLOGICAL INFORMATION

Product AS SOLD

Ecotoxicity

Environmental Effects : Harmful to aquatic life.

Product

Toxicity to fish : no data available
Toxicity to daphnia and other : no data available

SAFETY DATA SHEET

SOLID POWER XL

aquatic invertebrates

Toxicity to algae : no data available

Components

Toxicity to daphnia and other aquatic invertebrates : sodium hydroxide
48 h EC50: 40 mg/l

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Product AS SOLD

Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

The product should not be allowed to enter drains, water courses or the soil.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Product AT USE DILUTION

Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (NZ_DG)

UN number : 1823
Description of the goods : SODIUM HYDROXIDE, SOLID
Class : 8
Packing group : II
Hazchem Code : 2W

SAFETY DATA SHEET

SOLID POWER XL

Environmentally hazardous : No

Sea transport (IMDG/IMO)

UN number : 1823
Description of the goods : SODIUM HYDROXIDE, SOLID
Class : 8
Packing group : II
Marine pollutant : No

Special precautions for user : None

Product AT USE DILUTION

Not intended for transport.

Section: 15. REGULATORY INFORMATION

Product AS SOLD

HSNO Approval Number : HSR002526

HSNO Group Standard : Cleaning Products (Corrosive) Group Standard 2006.

The components of this product are reported in the following inventories:

Switzerland. New notified substances and declared preparations :
not determined

United States TSCA Inventory :
On TSCA Inventory

Canadian Domestic Substances List (DSL) :
All components of this product are on the Canadian DSL.

Australia. Industrial Chemical (Notification and Assessment) Act :
On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand :
On the inventory, or in compliance with the inventory

Japan. ENCS - Existing and New Chemical Substances Inventory :
not determined

Japan. ISHL - Inventory of Chemical Substances (METI) :
not determined

Korea. Korean Existing Chemicals Inventory (KECI) :
not determined

Philippines Inventory of Chemicals and Chemical Substances (PICCS) :
On the inventory, or in compliance with the inventory

China Inventory of Existing Chemical Substances :
On the inventory, or in compliance with the inventory

Section: 16. OTHER INFORMATION

Issuing date : 09.10.2014
Version : 1.0

SAFETY DATA SHEET

SOLID POWER XL

Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.