SAFETY DATA SHEET



POG

CLEANING SYSTEMS LIMITED

Catalogue number: **FT482** Version No: **1.3** Issue date: **13/01/2017**

Safety Data Sheet according to WHS ADG and HSNO requirements

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	POG
Synonyms	FT482
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Paint, Oil and Grease Remover for Carpets & Hard Surfaces
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	LEANING SYSTEMS LIMITED	
Address	Great South Road, Penrose, Auckland 1061 NEW ZEALAND	
Telephone	D579 4114	
Fax	r64 9579 4115	
Website	www.deaningsystems.co.nz	
Email	rachel@deaningsystems.co.nz	

Emergency telephone number

Association / Organisation	National Poisons Information Centre	
Emergency telephone numbers	0800 764 766	
Other emergency telephone numbers	Emergency Services 111	

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

 ${\it HAZARDOUS\ CHEMICAL.\ NON-DANGEROUS\ GOODS.\ According\ to\ the\ WHS\ Regulations\ and\ the\ ADG\ Code.}$

HSNO Schedule	3.1D , 6.1E (All), 6.1E (D) 6.3B , 6.8A, 6.5B , 9.1B (All), 9.1B (C), 9.1B (F), 9.2C HSNO Approval HSR006398, 006482, 006637	
GHS Classification ^[1]	Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, STOT - SE (Resp. Irr.) Category 3, Reproductive Toxicity Category 1B, Skin Sensitizer Category 1, STOT - SE (Narcosis) Category 3	
Legend:	Legend: 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI	

Label elements

GHS label elements



SIGNAL WORD	DANGE

Hazard	statement(s)	

riamara otatomont(o)	
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H360D	May damage the unborn child.
H317	May cause an allergic skin reaction
H336	May cause drowsiness or dizziness
AUH019	May form explosive peroxides

Issue Date: 13/01/2017

Print Date: 13/01/2017

Product Code: FT482 POG
Version No: 1.3

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P271	se only outdoors or in a well-ventilated area.	
P280	ar protective gloves / eye protection / face protection.	
P261	void breathing mist / vapours / spray.	
P263	Avoid contact during pregnancy.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P305+P351+P338+P337+P313	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice / attention.	
P302+P362+P352+P333+P313	ON SKIN: Take off contaminated clothing and wash before reuse. Wash with plenty of soap and water. If skin irritation or rash occurs, get medical advice / ention.	
P304+P340+P312	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.	
P308+P313	8+P313 IF pregnant and exposed or concerned: Get medical advice / attention.	

Precautionary statement(s) Storage

P403+P405+P233 Store locked up, in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
111-76-2	30-<60	ethylene glycol monobutyl ether
872-50-4	10-<30	N-methyl-2-pyrrolidone
5989-27-5	10-<30	<u>d-limonene</u>

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Ingestion	If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.
Inhalation	If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation or rash.
Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If pain persists or recurs seek medical attention.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Product Code: FT482 Issue Date: 13/01/2017 Version No: 1.3 Print Date: 13/01/2017

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Advice for firefighters Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Fire Fighting Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. WARNING: In use may form flammable/ explosive vapour-air mixtures. Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit acrid smoke. Fire/Explosion Hazard Mists containing combustible materials may be explosive. On combustion, may emit toxic fumes of carbon monoxide (CO), carbon dioxide (CO2), nitrogen oxides (NOx) and other pyrolysis products typical of burning organic material May emit corrosive fumes WARNING: Long standing in contact with air and light may result in the formation of potentially explosive peroxides.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	Environmental hazard - contain spillage. Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate environmental hazard - contain spillage. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Absorb on sand, dirt, vermiculite or similar absorbent material. Place into labelled drums and dispose of according to local government regulations. Immediately notify emergency services (Police or Fire Brigade) if the spill is too large for you to safely and effectively handle.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

	•
	Product under certain conditions may form explosive peroxides when exposed to light and air. Unopened containers received from the supplier should be safe to store for 18 months. Opened containers should not be stored for more than 12 months.
	Avoid all personal contact, including inhalation.
	Wear protective clothing when risk of exposure occurs.
	Use in a well-ventilated area.
Safe handling	Prevent concentration in hollows and sumps.
Sale Hallulling	DO NOT enter confined spaces until atmosphere has been checked.
	Avoid smoking, naked lights or ignition sources.
	Avoid contact with incompatible materials.
	When handling, <mark>DO NOT</mark> eat, drink or smoke.
	Keep containers securely sealed when not in use.
	Avoid physical damage to containers.
	DO NOT allow clothing wet with material to stay in contact with skin
	Store in original containers.
	Keep containers securely sealed.
	No smoking, naked lights or ignition sources.
Other information	Store in a cool, dry, well-ventilated area.
	Store away from incompatible materials and foodstuff containers.
	Protect containers against physical damage and check regularly for leaks.
	Observe manufacturer's storage and handling recommendations contained within this SDS.

Issue Date: 13/01/2017

Print Date: 13/01/2017

Product Code: **FT482**Version No: **1.3**

Conditions for safe storage, including any incompatibilities

Suitable container	Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Certain of the ingredients may form unstable peroxides in storage. Avoid strong oxidising agents, strong acids and strong caustics.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethylene glycol monobutyl ether	2-Butoxyethanol	96.9 mg/m3 / 20 ppm	242 mg/m3 / 50 ppm	Not Available	Sk
Australia Exposure Standards	N-methyl-2-pyrrolidone	1-Methyl-2-pyrrolidone	103 mg/m3 / 25 ppm	309 mg/m3 / 75 ppm	Not Available	Sk

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethylene glycol monobutyl ether	Butoxyethanol, 2-; (Glycol ether EB)	20 ppm	20 ppm	700 ppm
N-methyl-2-pyrrolidone	Methyl 2-pyrrolidinone, 1-; (N-Methylpyrrolidone)	10 ppm	10 ppm	10 ppm
d-limonene	Limonene, d-	20 ppm	20 ppm	160 ppm

Ingredient	Original IDLH	Revised IDLH
ethylene glycol monobutyl ether	700 ppm	700 [Unch] ppm
N-methyl-2-pyrrolidone	Not Available	Not Available
d-limonene	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Maintain adequate ventilation at all times. In most circumstances natural ventilation systems are adequate. If ventilation is poor, then the use of a local exhaust ventilation system is recommended.
Personal protection	
Eye and face protection	Safety glasses with side shields OR Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. Lens should be removed at the first signs of eye redness or irritation. Lens should be removed in a clean environment only after workers have washed hands thoroughly.
Skin protection	See Hand protection below
Hands/feet protection	Wear chemical protective gloves, e.g. PVC, NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. Gloves must only be wom on clean hands.
Body protection	See Other protection below
Other protection	Overalls. P.V.C. apron. Barrier cream. Skin cleansing cream. Eye wash unit.

Issue Date: 13/01/2017

Print Date: 13/01/2017

Product Code: FT482
Version No: 1.3

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear colourless liquid		
Physical state	Liquid	Relative density (Water = 1)	0.937
Odour	Citrus odour	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit(%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Partly miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	The material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Ethylene glycol monobutyl ether penetrates the skin easily and will cause more harm on skin contact than through inhalation. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use
Eye	of the material and ensure that any external damage is suitably protected. This material can cause eye irritation and damage in some persons. Direct contact with the liquid may produce painful burning or stinging of the eyes and lids, watering and inflammation of the conjunctiva and temporary corneal clouding. Eye contact may cause tearing or blurring of vision.
Chronic	Vapour may cause mild eye irritation. Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Ample evidence exists, from results in experimentation that developmental disorders in unborn children are directly caused by human exposure to the material.

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Harmful to aquatic organisms. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol monobutyl ether	LOW (Half-life = 56 days)	LOW (Half-life = 1.37 days)
N-methyl-2-pyrrolidone	LOW	LOW
d-limonene	HIGH	HIGH

Product Code: FT482 **POG** Issue Date: 13/01/2017 Version No: 1.3 Print Date: 13/01/2017

Bio accumulative potential

Ingredient	Bioaccumulation
ethylene glycol monobutyl ether	LOW (BCF = 2.51)
N-methyl-2-pyrrolidone	LOW (BCF = 16)
d-limonene	HIGH (LogKOW = 4.8275)

Mobility in soil

Ingredient	Mobility
ethylene glycol monobutyl ether	HIGH (KOC = 1)
N-methyl-2-pyrrolidone	LOW (KOC = 20.94)
d-limonene	LOW (KOC = 1324)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / packaging disposal

Recycle containers whenever possible

Product residues and containers should be disposed of in accordance with local government regulations.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ETHYLENE GLYCOL MONOBUTYL ETHER (111-76-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

N-METHYL-2-PYRROLIDONE (872-50-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

D-LIMONENE (5989-27-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at: www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

Permissible Concentration-Time Weighted Average PC-TWA; PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Government Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit IDLH: Immediate Danger to Life or Health Concentrations

OSF: Odour Safety Factor NOAEL: No Observed Effects Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: Bio Concentration Factors **Biological Exposure Index**

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.